

Solar Frontier Europe GmbH

## Product Data Sheet SF170-S



### Electrical Characteristics

#### Electrical Performance at Standard Test Conditions (STC)\*1

		SF170-S
Nominal Power	P <sub>max</sub>	170 W
Power tolerance		+5 W / 0 W
Open circuit voltage	V <sub>oc</sub>	112.0 V
Short circuit current	I <sub>sc</sub>	2.20 A
Voltage at nominal power	V <sub>mpp</sub>	87.5 V
Current at nominal power	I <sub>mpp</sub>	1.95 A

#### Electrical Performance at Nominal Operating Cell Temperature (NOCT) Conditions\*2

		SF170-S
Nominal Power	P <sub>max</sub>	126 W
Open circuit voltage	V <sub>oc</sub>	102 V
Short circuit current	I <sub>sc</sub>	1.76 A
Voltage at nominal power	V <sub>mpp</sub>	82.1 V
Current at nominal power	I <sub>mpp</sub>	1.55 A

### Performance at Low Irradiance

Efficiency reduction of maximum power from an irradiance of 1,000 W/m<sup>2</sup> to 200 W/m<sup>2</sup> at 25 °C is typically 2.0 %. The standard deviation for the reduction of efficiency is 1.9 %.


\*1 Standard Test Conditions (STC): 1,000 W/m<sup>2</sup> irradiance, module temperature 25 °C, air mass 1.5. I<sub>sc</sub> and V<sub>oc</sub> are ±10 % tolerance of STC rated values. Module output may rise due to the Light Soaking Effect. Subject to simulator measurement uncertainty (using best-in-class AAA solar simulator and applying Solar Frontier preconditioning requirements): +10 % / -5 %.

\*2 Nominal Operating Cell Temperature Conditions: Module operating temperature at 800 W/m<sup>2</sup> irradiance, air temperature 20 °C, wind speed 1 m/s and open circuit condition.



## Typical I-V Characteristics at STC

I-V P-V Characteristics by Irradiance  
 Model: SF170-S  
 Condition: AM 1.5 / 25 °C




Typical characteristics

## Thermal Characteristics

NOCT	47 °C
Temperature coefficient of Isc	+0.01 %/K
Temperature coefficient of Voc	-0.30 %/K
Temperature coefficient of Pmax	-0.31 %/K

These thermal characteristics are typical data.

I-V Characteristics by Temperature  
 Model: SF170-S  
 Condition: AM 1.5 / 1,000 W/m²



Typical characteristics

## Characteristics for System Design

Maximum system voltage	V <sub>sys</sub>	1,000 V DC (UL 600 V DC)
Limiting reverse current	I <sub>r</sub>	7 A
Maximum series fuse rating	I <sub>sf</sub>	4 A

## Mechanical Characteristics

Dimensions (L x W x H)* <sup>3</sup>	1,257 x 977 x 35 mm (49.5 x 38.5 x 1.4 inch)	
Weight	20 kg (44.1 lbs)	
Module operating temperature	-40 °C to 85 °C	
Application class on IEC61730	Class A	
Fire safety class on IEC61730	Class C	
Safety class on IEC61140	II	
Snow load (to the front of the module)* <sup>4</sup>	2,400 Pa (IEC61646) / 1,600 Pa design load (UL1703)	
Wind load (to the back of the module)	2,400 Pa (IEC61646) / 1,600 Pa design load (UL1703)	
Cell type	CIS substrate glass (cadmium free)	
Front cover	Clear tempered glass, 3.2 mm	
Encapsulant	EVA	
Back sheet	Weatherproof plastic film (color: black & silver)	
Frame	Anodized aluminum alloy (color: black)	
Edge sealant	Butyl rubber	
Junction box	Protection rating: IP67 (with bypass diode)	
Adhesive	Silicone	
Output cables (Conductor)	2.5 mm <sup>2</sup> / AWG14 (halogen free)	
Cable lengths (symmetrical)	1,200 mm (47.2 inch)	
Connectors	MC4 compatible	

## Qualifications and Compliance

IEC 61646 / IEC 61730 / UL 1703 / MCS 005-2.3

CE-Mark declaration

Solar Frontier is certified as: ISO 9001 / ISO 14001 / OHSAS 18001


RoHS compliant

\*3: Dimensional tolerances are stated in the drawing section of this product data sheet.

\*4: UL - 1.5 times design load is applied to the module. Accordingly, 2,400 Pa (50.1 lbs /ft<sup>2</sup>) is loaded to test the 1,600 Pa (33.4 lbs /ft<sup>2</sup>) UL design load.



## Module drawing



No.	Item	QT'Y	Description
1	Cell	1	CIS (Substrate glass)
2	Cover glass	1	Clear tempered glass
3	Encapsulant		EVA
4	Back sheet		Weatherproof plastic film (color: black & silver)
5	Frame	1 Set	Anodized aluminium alloy (color: black)
6	Edge sealant		Butyl rubber
7	Junction box	1	With bypass diode
8	Cable		2.5 mm <sup>2</sup> / AWG14 (with waterproof and locking connector)
9	Adhesive		Silicone
10	Label	1	Product label
11	Screw	8	Stainless tapping (SUS304J3)
12	Bar code label	1	Serial number

### Europe

### Italy

### Asia (HQ)

### Middle East

### Americas

Solar Frontier Europe GmbH  
Bavariafilmpfad 8  
82031 Grünwald bei München  
Germany

Solar Frontier Europe GmbH  
Sede Secondaria per l'Italia  
Via Domenico Cotugno 49/A scala B  
70124 Bari  
Italy

Solar Frontier K.K.  
Daiba Frontier Building  
2-3-2 Daiba, Minato-ku  
Tokio 135-8074  
Japan

Solar Frontier K.K.  
Technical & Scientific Office  
Eastern Cement Tower, #306  
King Fahd Road  
Al Khobar  
Kingdom of Saudi Arabia  
Tel: +966 3882 0260

Solar Frontier Americas Inc.  
3945 Freedom Circle  
Santa Clara, CA 95054  
USA  
Tel: +1 408 916 4150

Tel: +49 89 92 86 142 0

Tel. +39 080 89 66 984

Tel: +81 3 5531 5626

[www.solar-frontier.com](http://www.solar-frontier.com)  
[www.solar-frontier.eu](http://www.solar-frontier.eu)

Copyright for all material appearing on this Product Data Sheet belongs to Solar Frontier. Solar Frontier reserves the right, at its sole discretion, to change, modify, add, or delete portions of the content at any time without notice, but makes no commitment to update any content which may be out of date. The data contained in this Product Data Sheet indicates nominal data of our products as of the shipment of the products. Any warranty with respect to the quality or performance of our products will be provided only based on a limited warranty certificate separately issued by Solar Frontier. See the Installation and Maintenance Guide or contact the Technical Service for further information on approved installation and use of this product.